

# S70G Handheld GNSS RTK Rugged Android GNSS RTK



# S70G

# Android Handheld GNSS RTK

S70G is a 4-constellation dual frequency GNSS system (GPS, GLONASS, GALILEO and BEIDOU) that allows to collect data and photos in the field, in an easy and fast way.

It is supplied with an antenna connected directly to the tablet which guarantees 2cm accuracy, but if required, connecting an external antenna it gains even more precise data.

S70G is equipped with Android 10 operating system and has a highly detailed WUXGA resolution (1920x1200) display for greater detail quality. The 8000mAh battery allows the instrument to work over 8 hours and the IP67 protection makes the device suitable for any environment. S70G is able to work in real time through the reception of RTK corrections, transmitted by a network of GNSS Permanent Stations.

Besides working in real time, it can also record raw data received from satellites for post-processing in the office. This allows the operator to achieve greater precision, enabling to work even in areas where there is not a good coverage of the GSM signal.





# **4-CONSTELLATION SYSTEM**

Stonex S70G has a dual frequency GNSS chip integrated that uses all 4 Constellations: GPS, GLONASS, GALILEO, BEIDOU; all included, no additional cost.



# **ANDROID SYSTEM**

The receiver is managed by the Android 10 operating system with a simple and intuitive interface.



# HIGH QUALITY DISPLAY

The high quality 8" display has a WUXGA resolution (1920x1200) with 500 Nits brightness.



# RTK AND POST-PROCESSING

S70G can work in real time with RTK corrections and simultaneously record the raw data for post-processing.



# RUGGED

With IP67 Certification Stonex S70G will ensure operations in extremely tough environments.





# S70G GNSS RTK

# Compact and portable for GIS and Survey applications



Cube-a is the Stonex surveying and mapping software designed and developed for Android platform.

Thanks to the flexibility of the Android environment, we have been able to create a simple and intuitive user interface that makes surveyors ready for any work, saving time and increasing productivity.

Full support for touch gestures and the possibility to install it on Smartphones and Tablets are the keys to the success of Cube-a. It also includes support for many languages and adjusts its interface as from the current system language setting.

Cube-a is a modular application which can be customized as needed: GNSS, Robotic and Classic Total Stations, GIS and 3D Modelling modules can be enabled to fulfill any customer need.

## Cube-a is available in three versions:

- Cube-a for GNSS
- Cube-a for GNSS+GIS
- Cube-a for Mechanical and Robotic Total Stations.

# © cube·connector

This is an Android APP and it has been developed to connect Android devices to Stonex GNSS receivers. In order to be connected to the GNSS, the Android Smartphone / Tablet must be paired with the GNSS by Bluetooth.

Once the Bluetooth connection has been established, Cube-connector will replace the GNSS readings from the internal device with the ones from the Stonex GNSS receiver.

With the Stonex S70G, through Cube-connector, any customer can easily use his software for GIS / Survey in the Android operating system. Our application will manage all settings and configurations with integrated precision GNSS and will make the correct coordinates available for third-party software.



# **S70G TECHNICAL FEATURES**

RECEIVER		
	GPS: L1 C/A, L2C	
Catallita signals treaked	GLONASS: L1, L2	
Satellite signals tracked	BEIDOU: B1, B2	
	GALILEO: E1, E5b	
	SBAS: L1	-
Channels	184	
Position Rate	Up to 10 Hz	
Protocol	RTCM 3.3	
Signal Reacquisition	< 1 s	
RTK Signal Initialization	Typically < 10 s	

Typically < 15 s

> 99.9 %

POS		INI	
P( )	IC JIN	ши	( 7

Initialization Reliability

Hot Start

	STATIC SURVEYING	
	Horizontal	5 mm + 1 ppm RMS
	Vertical	10 mm + 1 ppm RMS
	REAL TIME KINEMATIC <sup>2</sup> -	SA65 ANTENNA
	Fixed RTK Horizontal	10 mm + 1 ppm RMS
ĺ	Fixed RTK Vertical	20 mm + 1 ppm RMS
	REAL TIME KINEMATIC <sup>2</sup> -	SA15 ANTENNA
	Fixed RTK Horizontal	20 mm + 1 ppm RMS
	Fixed RTK Vertical	30 mm + 1 ppm RMS
	SBAS accuracy	< 60 cm

#### **SYSTEM**

Processor	SDM632	
Operating System	Android 10	
RAM	4GB	
Flash Memory	64GB	
External Storage	SDHC supported Micro SD	

#### DISPLAY

Display	8" TFT color, Capacitive	
Resolution	1920 × 1200 WUXGA	
Brightness	500 Nits	

# **CAMERA**

CHITCH		
Rear	13 MP	
Front	5 MP	

## **INTERNAL MODEM**

LTE FDD:

B1/B2/B3/B4/B5/B7/B8/B17/

B20/B28

Network LTE TDD: B38/B39/B40/B41

WCDMA: B1/B2/B5/B8 GSM: B2/B3/B5/B8 Dual SIM card

Accuracy and reliability are generally subject to satellite geometry (DOPs), multipath, atmospheric
conditions and obstructions. In static mode they are subject even to occupation times: the longer is
the Baseline, the longer must be the occupation time.

2. Network RTK precision depends on the network performances and are referenced to the closest

Battery life and charging time depend on the user's scenario. Time may vary based on factors such as screen brightness, apps, software, power management, battery condition, etc.

Illustrations, descriptions and technical specifications are not binding and may change

**INTERNAL SENSOR** 

G-Sensor	Yes	
E-Compass	Yes	
Gyroscope	Yes	
Light Sensor	Yes	

#### COMMUNICATION

I/O Connectors	High speed USB Type-C OTG port Connector for external antenna	
Bluetooth	4.1	
Wi-Fi	802.11 a/b/g/n/ac	
NFC	Yes	

### **POWER SUPPLY**

Detter	Rechargeable and replaceable
Battery	3.8 V - 8000 mAh
Working Time <sup>3</sup>	Up to 8 hours in operating mode
	Up to 12 hours in energy saving mode
Charge Time <sup>3</sup>	Typically < 5 hours

### PHYSICAL SPECIFICATION

THI GIGHT CHILDIN		
Dimensions	235 mm x 146 mm x 13 mm	
Weight	690 g (with battery)	
Operating Temperature	-20°C to 60°C (-4°F to 140°F)	
Storage Temperature	-30°C to 70°C (-22°F to 158°F)	
Waterproof/Dustproof	IP67	
Shock Resistance	1.2 m drop resistant	

# STANDARD ACCESSORIES

Antenna GNSS SA15, Battery, Charger, Strap, Softbag

# **OPTIONAL ACCESSORIES**

2m Carbon fiber pole, Antenna GNSS SA65, Antenna cable, Bracket for pole, Battery, Battery charger, Car charger adaptor



